

DS-2CD4B25G0-IZS

2MP Smart Bullet Network Camera



smart IPC

The smart network bullet camera DS-2CD4B25G0-IZS offers 1920 × 1080 resolution, 120dB WDR, Auto-iris, PoE, Defog, EIS, 3D DNR, Digital zoom 12x, 6 behavior analyses, 3 exception detection, and 1 recognition to meet a wide variety of applications.

- 1/2.8" Progressive Scan CMOS
- Auto-iris
- 1920 × 1080 @ 30fps
- H.265, H.265+
- 120dB WDR
- IP67
- 6 behavior analyses, 3 exception detection, and 1 recognition



Specifications

Camera	
Image Sensor	1/2.8" Progressive Scan CMOS
Min. Illumination	0.005 Lux @ (F1.2, AGC ON) 50 IRE, 0.007 Lux @ (F1.4, AGC ON) 50 IRE
Shutter Speed	1/3 s – 1/100,000 s
Slow Shutter	Yes
Lens Mount	Integrated
Auto-iris	DC drive
Day & Night	IR Cut Filter
Digital Noise Reduction	3D DNR
WDR	120dB
3-Axis Adjustment (Bracket)	Pan: 0° to 360°, tilt: 0° to 90°, rotate: 0° to 360°
Lens	
Focal length	4.7 to 65.8 mm @ F1.4 motorized zoom and focus, configurable by browser
Focus	Auto
FOV	4.7 to 65.8 mm @F1.4, horizontal FOV 54.84° to 3.12°, vertical FOV 31.62° to 1.76°, diagonal FOV 62.08° to 3.58°
Lens Mount	Integrated
IR	
IR Range	Up to 120 m
Wavelength	850nm
Compression Standard	
Video Compression	Main stream: H.265/H.264 Sub stream: H.265/H.264/MJPEG Third stream: H.265/H.264
H.264 Type	Baseline Profile/Main Profile/High Profile
H.264+	Support
H.265 Type	Main Profile
H.265+	Support
Video Bit Rate	32 Kbps – 16 Mbps (VBR/CBR)
Audio Compression	G.711/G.722.1/G.726/MP2L2/PCM
Audio Bit Rate	64Kbps(G.711)/16Kbps(G.722.1)/16Kbps(G.726)/32-192Kbps(MP2L2)
Image	
Max. Resolution	1920 × 1080
Main Stream	50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720) 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720)
Sub Stream	50Hz: 25fps (640 × 480, 640 × 360, 320 × 240) 60Hz: 30fps (640 × 480, 640 × 360, 320 × 240)
Third Stream	50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 576, 640 × 480, 640 × 360, 352 × 288, 320 × 240) 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 480, 640 × 480, 640 × 360, 352 × 240, 320 × 240)
Image Enhancement	BLC/HLC/3D DNR/Defog/EIS
Image Setting	Rotate Mode, Saturation, Brightness, Contrast, Sharpness, AGC, White Balance adjustable by client software or web browser
Region of Interest	Support 4 fixed region for each stream, and dynamic face tracking

Target Cropping	Yes
SVC	H.264 and H.265 encoding
Day/Night Switch	Day/Night/Auto/Schedule/Triggered by Alarm In
Picture Overlay	LOGO picture can be overlaid on video with 128 × 128 24bit bmp format
Network	
Network Storage	Support Micro SD/SDHC/SDXC card (128G), local storage and NAS (NFS,SMB/CIFS), ANR
Alarm Trigger	Motion detection, video tampering alarm, network disconnected, IP address conflict, illegal login, HDD full, HDD error
Protocols	ARP, UDP/IP, TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, CoS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP™, SMTP, SNMPv1/v2/v3, IGMP, QoS, IPv4, IPv6, 802.1x
Simultaneous Live View	Up to 20 channels
Client	iVMS-4200, iVMS-4500, iVMS-5200, Hik-connect
General Function	One-key reset, anti-flicker, three streams, heartbeat, mirror, password protection, access log, privacy mask, watermark, IP address filter
API	ONVIF (PROFILE S, PROFILE G), Open-SDK (for third-party apps), ISAPI
Web Browser	IE8+, Chrome31.0-44, Firefox30.0-51, Safari8.0+
Interface	
Audio	1 input (line in/mic in), 1 output (line out), mono
Communication Interface	1 RJ45 10M/100M Ethernet port; 1 RS-485 interface
Alarm	1 input, 1 output (up to 24 VDC 1A or 110 VAC 500mA)
Video Output	1Vp-p composite output (75 Ω/BNC)
On-board storage	Built-in Micro SD/SDHC/SDXC slot, up to 128 GB
Reset Button	Yes
Audio	
Environment Noise Filtering	Support
Audio Sampling Rate	8 kHz/16 kHz/32 kHz/44.1 kHz/48 kHz
Smart Feature-set	
Behavior Analysis	Line crossing detection, intrusion detection, region entrance detection, region exiting detection, unattended baggage detection, object removal detection
Line Crossing Detection	Cross a pre-defined virtual line, up to 4 pre-defined virtual lines supported
Intrusion Detection	Enter and loiter in a pre-defined virtual region, up to 4 pre-defined virtual regions supported
Region Entrance Detection	Enter a pre-defined virtual region from the outside place
Region Exit Detection	Exit from a pre-defined virtual region
Object Removal Detection	Objects removed from the pre-defined region, such as the exhibits on display.
Unattended Baggage Detection	Objects left over in the pre-defined region such as the baggage, purse, dangerous materials
Exception Detection	Scene change detection, defocus detection, audio exception detection
Recognition	Face detection
Statistics	Counting
General	
Operating Conditions	-30 °C to 60 °C (-22 °F to 140 °F), Humidity 95% or less (non-condensing)
Power Supply	12 VDC ± 20%, PoE (802.3at, class 4), three-core terminal blocks
Power Consumption and Current	12 VDC ± 20%: Max. 12 W/1 A PoE (802.3at, 42.5V-57V), 0.2 A to 0.3 A
Protection Level	IP67 TVS 4000V Lightning Protection, Surge Protection and Voltage Transient Protection
Regulatory Information	FCC, CE, UL, 100% PVC Free, RoHS, WEEE



Dimensions	Camera: 348.38 × 114.18 × 111.73 mm (13.72" × 4.5" × 4.4") With package: 386 × 156 × 155 mm (15.2" × 6.1" × 6.1")
Weight	Camera: 1740 g (3.8 lb.) With package: 2125 g (4.7 lb.)

Available Models:

DS-2CD4B25G0-IZS

(1 audio input (line in/mic in), 1 audio output, 1 RS-485, 1 alarm input and 1 alarm output)

Dimensions



Unit: mm (")

Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
sateru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com