

DS-D4515CK-1FP
135 inch AIO LED



- Highly integrated and compatible cabinet, simple and lightweight design, slimmer appearance and lighter body.
- Convenient pre-maintenance, elegant sense of style: the system board is placed under the card to achieve a truly comprehensive pre-maintenance, fast and convenient installation; under the profile of light luxury fabric layer, both industrial aesthetics and high-end style, suitable for all kinds of conference scenes.
- Highly integrated design, integrated presentation: Built-in 2*20W professional speakers, support OPS module (Optional) , Android/Windows (Optional) dual system free switching, highly integrated, intelligent integration.
- Fluid and non-lagging, new paradigm of interaction: the internal platform is comprehensively upgraded, with surging power to support smooth operation experience; equipped with self-developed Wonder OS 3.0 system, professionally adapted to large-screen interaction; multi-terminal easy wireless casting, exploring more possibilities of collaboration.
- High-precision die-casting cabinet structure design, supporting the front disassembly of LED module, power supply and receiver card.
- The soldering joints are made of lead-free and non-toxic solder paste, which will not cause harm to the human body and the environment.

▪ Datasheet

Cabinet	
Pixel Structure	COB
Pixel Pitch	1.50 mm
Pixel Density	409600 dots/m ²
Maintenance	Front
Display	
Color temperature	3000-10000 K
Viewing Angle	178°(H)/178°(V)
Display Size	135 inch
Physical Resolution	1920 × 1080
Brightness	500 cd/m ²
Color Depth	22 bit
Contrast Ratio	15000: 1
Refresh Rate	3840 Hz
System	
Operating System	Android 12.0
CPU	A76 × 4 + A55 × 4
RAM	16 G
Internal Storage	256 G
NIC	Built-in Gigabit LAN card with routing support
Frequency	2.4 GHz
Wireless	Support Station and AP at the same time, support hotspot function
Bluetooth	Built-in BLE low power Bluetooth module, supports Bluetooth version 5.1 and below
Audio	
Speaker	2 × 20 W
Port	
Audio/Video Input Interface	LINE IN × 1, HDMI IN × 4
Audio/Video Output Interface	LINE OUT × 1, SPDIF OUT × 1, HDMI OUT × 1
Network Interface	RJ45 × 1
Data Transfer Interface	Front: USB3.0 × 2, Type-C × 1 Bottom: USB2.0 × 1
Control Interface	RS232 × 1
Process	
Drive Method	Constant Current Driver
Power	
Power Supply	100~240 VAC, 50/60 Hz
Peak Power Consumption	≤ 2000 W
Average Power Consumption	< 670 W

Common Parameter	
Product Size	3048.1 (W) mm × 2519.87 (H) mm × 733.56 (D) mm (Includes Base) 3048.1 (W) mm × 1832 (H) mm × 53.6 (D) mm (Without Base)
Mounting Type	Wall mounting / Mobile bracket mounting
Packing List	Network Cable, Remote Control, Anti-static gloves, Spare parts IC, L5.0/M4/Hexagonal Spanner, Screws
Gross Weight	227.3 kg
Net Weight	144.0 Kg

见远 行更远

See Far, Go Further



online小程序



国内公众号



服务公众号



企业微信

杭州海康威视数字技术股份有限公司
HANGZHOU HIKVISION DIGITAL TECHNOLOGY CO., LTD.

海康威视官网 <https://www.hikvision.com/cn/>
海康威视合作伙伴平台 <https://partners.hikvision.com/>
服务热线 400-800-5998 (7*24小时)

©杭州海康威视数字技术股份有限公司。除非另有约定，我们不对本手册提供任何明示或默示的声明或保证。我们保留修改的权利，恕不另行通知。