

**DS-D4015CS-1F COB****DS-D4015CS-1F COB, 1.538mm, 640\*480MM**


- High refresh rate and Ultra-high contrast ratio, more delicate and smooth video, and more realistically image with excellent color performance
- 4:3 ratio cabinet, best choice for high cost performance
- Highly integrated and compatible cabinet with simple and lightweight design
- Ultra-thin backshell for easier installation, easier to level the lamp boards, and make the splicing more flat
- Modular structure design, support module, power supply, receiver card front maintenance

## ▪ Specification

<b>Product Model</b>	
Product Model	DS-D4015CS-1F (COB) / Module: DS-D4015CS-1F/ASQ Cabinet: DS-D40S-1F/S
<b>Product Type</b>	
Product Type	Indoor small pitch full color LED
<b>Cabinet</b>	
Pixel Pitch Category	P1.5
Pixel Pitch	1.538 mm
Pixel Density	422500 dots/m <sup>2</sup>
Modules Component	2 × 3
Resolution	416 × 312
Dimensions (W × H × D)	640 (W) mm × 480 (H) mm × 36 (D) mm (25.197" × 1.898" × 1.42")
Area	0.3072 m <sup>2</sup>
Weight	6 kg (13.23 lb.)
Cabinet Material	Die cast aluminum
Maintenance Method	Complete front maintenance
<b>Module</b>	
Dimensions	320×160 mm
Module Resolution	208 × 104
Surface	COB
IP Ratings	Front IP40
<b>Display</b>	
White Balance Brightness	600 cd/m <sup>2</sup>
Color Temperature	3000-10000 K adjustable
Viewing Angle	160°(H)/160°(V)
Contrast Ratio	5000:1
Color Uniformity	≤ ± 0.003Cx, Cy
Brightness Uniformity	≥ 97%
Life Span	100000 Hours
<b>Processing Performance</b>	
Driving Method	Constant current driving
Frame Frequency	60 Hz
Refresh Rate	3840 Hz
Grey Level	Up to 16 bit
Color Depth	Up to 16 bit
<b>Power</b>	
Max. Consumption	≤450W/m <sup>2</sup>
Average Consumption	≤150W/m <sup>2</sup>
Input Voltage	100~240 VAC ± 10%
<b>Working Environment</b>	
Working Temperature	-10 °C to 50 °C (14 °F to 122 °F )
Working Humidity	10% to 60% RH (without condensation)
Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F )

Storage Humidity	10% to 85% RH (without condensation)
<b>General</b>	
Package Dimensions (W × H × D)	758 (W) mm × 606 (H) mm × 442 (D) mm (29.843 " × 23.858 " × 17.402 " )
Packing List	Regulatory Compliance and Safety Information × 1 Several Joint pieces, Fixing screws and Signal cables Several LED lamp beads and IC components
Gross Weight	7 kg (15.4 lb.)
Net Weight	6 kg (13.23 lb.)
<b>Bracket</b>	
Modular Bracket	DP-D40XCA23-1X1-Q0.3-NW-Q0.3-HC 1*1; DP-D40XCA23-2X2-Q1-NW-Q1-HC 2*2

### Dimension



### Accessory

#### Optional

DS-D40S-1F/S	DS-D40S-2F	DS-D40W-2F/PC	DS-1NP6UEC0	DS-D40S-2F/H

# See Far, Go Further



[www.hikvision.com](http://www.hikvision.com)  
[support@hikvision.com](mailto:support@hikvision.com)

