

**DS-VP41D-C/HW7L
Tower Workstation**



- Integrated graphics with great decoding capabilities
- Four-screen independent output for efficient management
- Pre-installed operating system and configured with keyboard and mouse, plug and play
- Operates in extreme temperatures and high humidity
- Customized dust filters for effective protection against windborne sand and dust

▪ Specification

Hardware Specifications	
CPU	i7-14700, 5.4 GHz, 33 MB Cache, 20 Cores
Memory	Standard Config: 16GB, DDR5, 4400MT/s Expandable up to 128GB.
Hard Disks	Standard Config: 512 GB, M.2 2280, Gen 4 PCIe NVMe, SSD 2 TB, 7200 RPM, 3.5 inch, SATA, 6Gb/s (Storage)
Supported Operating Systems	Win11 multilingual version pre-installed
Graphic Card	Standard Config: NVIDIA® T1000, 8 GB GDDR6 Graphic card
PCIe Slots	1*PCIe 4.0 x16 Slot, 1 M.2 For storage, 1M.2 for wireless
Ports	
Type-C	4
USB 3.0	2 (Front) +2 (Rear)
USB 2.0	2 (Rear)
Display Port	2
Microphone in	1
Audio out	1
Ethernet Port	1 x LAN 10/100/1000
VGA	/ (HDMI port can be used as VGA port)
HDMI	1
DP	1 (DP port can be used as HDMI port)
General	
Net Weight	5.63 kg (12.42 lb)
Gross Weight	6.72 kg (14.81 lb)
Dimension (W × H × D)	92.60 mm × 290.00 mm × 292.80 mm (3.65" × 11.42" × 11.53")
Package Dimensions (W × H × D)	394.00 mm × 264.00 mm × 487.00 mm (15.51" × 10.39" × 19.17")
Operating Temperature	5 °C to 45 °C (41 °F to 113 °F)
Storage Temperature	-40 °C to 70 °C (-40 °F to 158 °F)
Operating Humidity	20% to 80% (no condensation)
Storage Humidity	5% to 95% (no condensation)
Power Supply	300 W PSU, 92% Energy efficiency, 80 Plus Platinum
Form Factor	Tower SFF

▪ Available Model

DS-VP41D-C/HW7L

DS-VP41D-C/HW7L/FR

See Far, Go Further



www.hikvision.com
support@hikvision.com

