

DS-VP41D-C/HW7 Tower Workstation



- Graphics with great decoding capabilities
- Four-screen independent output for efficient management
- Pre-installed operating system and configured with keyboard and mouse, plug and play
- Operates in extreme temperatures and high humidity
- Customized dust filters for effective protection against windborne sand and dust



Specification

Hardware Specifications	
CPU	i7-14700, 2.10 GHz, 33 MB Cache, 20 Cores, 28 Threads
Memory	Standard Config: 2 × 32GB DDR5 DIMM/ 4 × 16GB DDR5 DIMM , 4400MT/s
	Scalability: 4 × 32GB DIMM
Hard Disks	Standard Config: 1 × 512GB M.2 NVMe SSD
	Scalability: 1 × 4TB 3.5inch SATA HDD
Supported Operating Systems	Windows 10 IoT/ Windows 10 Professional pre-installed
Graphic Card	Standard Config: NVIDIA T1000 8 GB GDDR6 / NVIDIA RTX 2060
PCIe Slots	1*PCle 4.0 x16 Slot 1*PCle 4.0 x4 Slot
Ports	
Type-C	1
USB 3.0	1 (Front) +3 (Rear)
USB 2.0	2 (Front) +2 (Rear)
Audio Port	1 Universal Audio port, 1 Audio line-out
Network Interface	1 x LAN 10/100/1000, Wi-Fi 6E
VGA	/ (HDMI port can be used as VGA port)
HDMI	1
DP	3 (DP port can be used as HDMI port)
General	
Operating Temperature	5 °C to 45 °C (41 °F to 113 °F)
Storage Temperature	-40 °C to 70 °C (-40 °F to 158 °F)
Operating Humidity	20% to 80% (no condensation)
Storage Humidity	5% to 95% (no condensation)
Power Supply	300 W PSU , 92% Energy efficiency , 80 Plus Platinum
Form Factor	Tower
Approval	CE, FCC
Accessories	Keyboard and Mouse

Available Model

DS-VP41D-C/HW7



Headquarters No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 www.hikvision.com

Follow us on social media to get the latest product and solution information.





HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision Corporate Channel

