

DS-VD22D-B/HW15/PAK VMS Server



- Innovate at scale with challenging and emerging workloads
- Increase efficiency and accelerate operations with autonomous collaboration
- Built-in proactive resilience through a complete portfolio of solutions

▪ Specification

Hardware Specifications	
CPU	Xeon Scalable processors 4410T (10 core 2.7GHz) ×2
Hard Disk	2TB 7.2K SATA×2(RAID_1)
Device Dimensions	Form factor: Rack (2U) Height : 86.8 mm (3.41 inches) Width :482 mm (18.97 inches) Depth : 707.78 mm (27.85 inches) without bezel 721.62 mm (28.4 inches) – with bezel For reference only
Memory	32GB DDR5×2 RDIMM
Storage Controller	SAS_H355
Power Supply	800 W (1 + 1)
Bezel	security bezel
Embedded Management	iDRAC9 iDRAC Direct iDRAC RESTful API with Redfish iDRAC Service Module Quick Sync 2 wireless module
OpenManage™ Software	OpenManage Enterprise OpenManage Power Manager plugin OpenManage SupportAssist plugin OpenManage Update Manager plugin
Integrations and Connections	Integrations: BMC Truesight; Microsoft System Center; OpenManage Integrations; Red Hat Ansible Modules; VMware vCenter and vRealize Operations Manager Connections: IBM Tivoli Netcool/OMNIBus; IBM Tivoli Network Manager IP Edition; Micro Focus Operations Manager; OpenManage Connections; Nagios Core; Nagios XI
Security	Cryptographically signed firmware Data at Rest Encryption (SEDs with local or external key mgmt) Secure Boot Secure Erase Secured Component Verification (Hardware integrity check) Silicon Root of Trust System Lockdown (requires iDRAC9 Enterprise or Datacenter) TPM 2.0 FIPS, CC-TCG certified, TPM 2.0 China NationZ
I/O & Ports	Front Ports: 1 x iDRAC Direct (Micro-AB USB) port, 1 x USB 2.0, 1 x VGA Internal Ports: 1 x USB 3.0 (optional) Rear Ports : 1 x Dedicated iDRAC Ethernet port, 1 x USB 2.0, 1 x USB 3.0, 1 x VGA, 1 x Serial (optional)
Supported Operating Systems	Not configured by default
Physical and Environmental Parameters	
Net Weight (without package)	28.6 kg (63.00 lb.)
Gross Weight (with package)	37.2 kg (82.01 lb.) For reference only

▪ **Available Model**

DS-VD22D-B/HW15

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

