

DS-D2055UL-1B(H)
LCD Display

The DS-D2055UL-1B(H) LCD display uses an industry-level ultra-narrow bezel design, which enables a bezel width of 3.5 mm between neighboring displays. The adopted direct-lit LED backlighting technology helps achieve ultra-high and uniform brightness of 500 cd/m² without boundary shadows. The display has abundant interfaces for video inputs, such as DVI, VGA, HDMI, and DP.


- 4K signal input, auto loop up to 30 screens with HDMI interfaces
- Switching between three picture modes: Monitoring, Meeting, and Movie
- Factory calibration for color and brightness uniformity
- Direct-lit LED backlight with uniform brightness and no boundary shadows
- 1920 × 1080 resolution, 178° viewing angle
- Ultra-narrow 3.5 mm bezel design
- Anti-glare, high definition, high brightness, high color gamut, and vivid images with rich colors
- Stable and 24-hour continuous working
- Metal casing for preventing from radiation and magnetic & electric field interference
- Wall-mount and modular brackets available to meet various installation requirements

▪ Specification

Display	
Screen Size	55 inch
Active Display Area	1209.6 (H) mm × 680.4 (V) mm
Backlight	Direct-lit LED backlight
Pixel Pitch	0.63 mm
Physical Seam	3.5 mm
Bezel Width	2.3 mm (top/left), 1.2 mm (bottom/right)
Resolution	1920 × 1080@60 Hz (downward compatible)
Brightness	500 cd/m ²
Viewing Angle	Horizontal 178°, vertical 178°
Color Depth	1.07B, 10bit
Contrast Ratio	4000:1
Response Time	7.5 ms
Color Gamut	72% NTSC
Surface Treatment	Haze 25%,2H
Interface	
Video & Audio Input	HDMI × 1, DVI × 1, VGA × 1, DP× 1, USB × 1
Video & Audio Output	HDMI × 1
Control Interface	RS232 IN × 1, RS232 OUT × 1
Power	
Power Supply	90-260 VAC, 50/60 Hz
Power Consumption	≤ 190 W
Standby Consumption	≤ 0.5 W
Working Environment	
Working Temperature	0°C to 50°C (32°F to 122°F)
Working Humidity	10% RH to 90% RH (non-condensing)
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Storage Humidity	10% RH to 90% RH (non-condensing)
General	
Casing Material	SGCC
VESA	600 (H) mm × 400 (V) mm / 580(H) mm × 460(V) mm
Product Dimension (W × H × D)	1213.5 (W) mm × 684.5 (H) mm × 71.19 (D) mm (47.78" × 26.94" × 2.8")
Package Dimension (W × H × D)	1404 (W) mm × 910 (H) mm × 231 (D) mm (55.28" × 35.83" × 9.09")
Net Weight	24.3 ± 0.5 kg (53.6 ± 1.1 lb) for single display
Gross Weight	42.9 ± 0.5 kg (94.6 ± 1.1 lb) for carton with a single display
Packing List	Carton with a single display : LCD display × 1, power cable × 1, network cable × 1, 2-meter HDMI cable × 1, screw × 4, remote control × 1, IR receiver × 1, RS-232 converter × 1, quick start guide (multilingual) × 1, quick start guide (English) × 1

▪ **Physical Interface**


Interface	Description	Interface	Description
POWER	Power indicator	DVI IN	DVI-I input interface for digital signals
LINE OUT	Audio output interface for analog signals	RS 232 OUT	Serial loopback output interface
HDMI OUT	HDMI output interface for digital signals	RS 232 IN	Serial input interface
HDMI IN	HDMI input interface for digital signals	USB	USB interface
DP IN	DP input interface for digital signals	IR IN	IR input interface
VGA IN	VGA input interface for analog signals	SWITCH	Switch button
90-260V~	Power input		



▪ **Available Model**

DS-D2055UL-1B(H)

▪ Dimension



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

